


## Features

- Various relays, including LED, test button
- With 2Z, 4Z contact forms
- With various terminal types
- Gilt contact types
- Transparent dust-proof cover, Various mounting types
- Various sockets available

## General-Purpose Relay



## Contact Ratings

Contact Ratings	2Z, 2H, 2D	4Z, 4H, 4D
Contact Resistance	50mΩ(1A 6VDC)	
Contact Material	Silver Alloy	
Contact capacity	10A/30VDC 250VAC	3A/30VDC 250VAC

## Specification

Insulation Resistance	500MΩ, 500VDC
Dielectric Strength	BCC 1500V 1 min
	BOC 1000V 1 min
	COC 1500V 1 min
Operate Time	25ms/25ms
Terminal Type	PCB, Socket


## Coil Ratings

Nominal Coil Power	0.9W/1.2VA
--------------------	------------

## Coil Versions

Nominal Voltage VDC	Pull-in Voltage VDC	Release Voltage VDC	Coil Resistance Ω: ±10%	Nominal Voltage VAC	Pull-in Voltage VAC	Release Voltage VAC	Coil Resistance Ω: ±10%
5	4.8	0.50	30	6	4.80	1.80	12
6	4.8	0.60	40	12	9.60	3.60	42
12	9.6	1.20	160	24	19.2	7.20	168
24	19.2	2.40	640	48	38.4	14.4	675
48	38.4	4.80	2560	110	96.0	36.0	3500
110	88.0	11.0	12100	220/240	176.0	66.0	14000/16500

## Dimension. Bottom View



## Reference Data



55.32



55.34