

SKKT 162 H4, SKKH 162 H4



SEMIPACK® 2

Thyristor / Diode Modules

SKKH 162 H4

SKKT 162 H4

Features


- Heat transfer through aluminium oxide ceramic isolated metal baseplate
- Hard soldered joints for high reliability
- UL recognized, file no. E 63 532

Typical Applications*

- DC motor control (e. g. for machine tools)
- Temperature control (e. g. for ovens, chemical processes)
- Professional light dimming (studios, theaters)

1) See the assembly instructions

V_{RSM} V 2100 2300	V_{RRM}, V_{DRM} V 2000 2200	$I_{TRMS} = 250 \text{ A}$ (maximum value for continuous operation) $I_{TAV} = 162 \text{ A}$ (sin.180; $T_c = 77^\circ\text{C}$) SKKT 162/20E H4 SKKT 162/22E H4	SKKH 162/20E H4 SKKH 162/22E H4	
I_{TAV}	sin. 180; $T_c = 85$ (100) $^\circ\text{C}$;		143 (101)	A
I_{TSM}	$T_{vj} = 25^\circ\text{C}; 10 \text{ ms}$ $T_{vj} = 125^\circ\text{C}; 10 \text{ ms}$		5200 4800	A A
i^2t	$T_{vj} = 25^\circ\text{C}; 8,3 \dots 10 \text{ ms}$ $T_{vj} = 125^\circ\text{C}; 8,3 \dots 10 \text{ ms}$		135000 115000	A ² s A ² s
V_T $V_{T(TO)}$	$T_{vj} = 25^\circ\text{C}; I_T = 500 \text{ A}$ $T_{vj} = 125^\circ\text{C}$		max. 1,65 max. 0,95	V V
r_T	$T_{vj} = 125^\circ\text{C}$		max. 2	mΩ
$I_{DD}; I_{RD}$	$T_{vj} = 125^\circ\text{C}; V_{RD} = V_{RRM}; V_{DD} = V_{DRM}$		max. 60	mA
t_{gd} t_{gr}	$T_{vj} = 25^\circ\text{C}; I_G = 1 \text{ A}; di_G/dt = 1 \text{ A}/\mu\text{s}$ $V_D = 0,67 * V_{DRM}$		1 2	μs μs
$(di/dt)_{cr}$ $(dv/dt)_{cr}$	$T_{vj} = 125^\circ\text{C}$ $T_{vj} = 125^\circ\text{C}$		max. 200	A/μs
t_q	$T_{vj} = 125^\circ\text{C}$,		max. 1000	V/μs
I_H	$T_{vj} = 25^\circ\text{C}; \text{typ. / max.}$		50 ... 150 150 / 400	μs mA
I_L	$T_{vj} = 25^\circ\text{C}; R_G = 33 \Omega; \text{typ. / max.}$		300 / 1000	mA
V_{GT}	$T_{vj} = 25^\circ\text{C}; \text{d.c.}$		min. 2	V
I_{GT}	$T_{vj} = 25^\circ\text{C}; \text{d.c.}$		min. 150	mA
V_{GD}	$T_{vj} = 125^\circ\text{C}; \text{d.c.}$		max. 0,25	V
I_{GD}	$T_{vj} = 125^\circ\text{C}; \text{d.c.}$		max. 10	mA
$R_{th(j-c)}$ $R_{th(j-c)}$ $R_{th(j-c)}$ $R_{th(c-s)}$	cont.; per thyristor / per module sin. 180; per thyristor / per module rec. 120; per thyristor / per module per thyristor / per module		0,16 / 0,08 0,17 / 0,085 0,19 / 0,095 0,1 / 0,05	K/W K/W K/W K/W
T_{vj}			- 40 ... + 125	°C
T_{stg}			- 40 ... + 125	°C
V_{isol} M_s M_t a m	a. c. 50 Hz; r.m.s.; 1 s / 1 min. to heatsink to terminal approx.		4800 / 4000 5 ± 15 % ¹⁾ 5 ± 15 % 5 * 9,81 175	V~ Nm Nm m/s ² g
Case	SKKT SKKH		A 21 A 22	






Fig. 1L Power dissipation per thyristor vs. on-state current




Fig. 1R Power dissipation per thyristor vs. ambient temp.




Fig. 2L Power dissipation per module vs. rms current




Fig. 2R Power dissipation per module vs. case temp.




Fig. 3L Power dissipation of two modules vs. direct current




Fig. 3R Power dissipation of two modules vs. case temp.

SKKT 162 H4, SKKH 162 H4




Fig. 4L Power dissipation of three modules vs. direct and rms current




Fig. 4R Power dissipation of three modules vs. case temp.




Fig. 5 Recovered charge vs. current decrease




Fig. 6 Transient thermal impedance vs. time




Fig. 7 On-state characteristics







Fig. 8 Surge overload current vs. time



This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

*IMPORTANT INFORMATION AND WARNINGS

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.