Product datasheet Characteristics

XKZA15100

potentiometer -10000 Ohm - for XKB XKD XKM

Price*: 380.05 GBP



| Product or component type | Controllers separate parts | |
|------------------------------------|--|--|
| Accessory / separate part category | Control accessories | |
| Product specific application | Medium hoisting applications Heavy hoisting applications Light hoisting applications | |
| Product compatibility | XKB XKD XKM | |
| Accessory / separate part type | Potentiometer | |
| Condition of use | For standard applications | |
| Ohmic value | 10000 Ohm | |
| Size | 15 mm | |
| Complementary | | |
| Standards | UTE 93-265 | |
| Potentiometer characteristic | Linear function Continuous rotational operation | |
| Operating angle | 360 ° | |
| Mechanical durability | 3000000 cycles | |
| Centre tap | Wired out to terminal | |
| Centre tap dead zone | 2 ° +/- 1 % | |
| Power dissipation in W | 3 W 85 °C | |
| Connections - terminals | Flying leads from soldered standard tags | |
| Product weight | 0.06 kg | |
| Environment | | |
| Mounting mode | By the body | |
| 0 | | |
| Offer Sustainability | DEACH Designation | |
| REACh Regulation | REACh Declaration | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration | |

Complementary

| Standards | UTE 93-265 | |
|------------------------------|--|--|
| Potentiometer characteristic | Linear function | 1 |
| | Continuous rotational operation | ¥ |
| Operating angle | 360 ° | |
| Mechanical durability | 3000000 cycles | |
| Centre tap | Wired out to terminal | 2. |
| Centre tap dead zone | 2 ° +/- 1 % | |
| Power dissipation in W | 3 W 85 °C | - S |
| Connections - terminals | Flying leads from soldered standard tags | ************************************** |
| Product weight | 0.06 kg | |
| | | |

Environment

| Mounting mode | By the body |
|---------------|-------------|

Offer Sustainability

| REACh Regulation | REACh Declaration |
|-------------------|--|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |

| China RoHS Regulation | Download RoHS China Declaration |
|-----------------------|---|
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Contractual warranty | |
| Warranty | 18 months |